

输油复合软管

A1-089



应用:

- 适用于油类与石油类产品，公路和铁路设备或固定安装设备上

优点:

- 使用于大部分石油产品
- 良好的弯曲半径
- 钢丝导静电

技术说明:

- 内部螺旋: 镀锌钢丝
- 内层: 聚丙烯薄膜
- 增强层: 聚丙烯层
- 外层: 外覆聚氯乙烯纤维布料, 黑色, 波纹状
- 外部螺旋: 镀锌螺旋钢丝
- 温度范围: -30°C至+100°C
- 导电性能: 螺旋钢丝导静电

适用标准及认证:

- BS 5842、EN 13765和ADR

适用标准及认证:

- 接头种类
- 接头材质: 铝, 碳钢, 不锈钢, 聚丙烯材质等
- 凸轮锁紧快速接头 (Camlock型)
- 固定或旋转的ISO PN10, ISO PN20

补充信息:

- 定制长度可按要求提供压力测试证书

Applications:

- Suction and discharge of light or heavy petroleum products and derivatives with aromatic content up to 100%. Road and rail equipment or fixed installations

Advantages:

- Both black and white oil can be carried
- Low bending radius
- Electrical conductivity ensured by the two helices which are attached to the couplings

Technical description:

- Internal helix: galvanized steel.
- Inner tube: polypropylene film.
- Reinforcement: polypropylene layers.
- Cover: PVC coated fabric, black, corrugated.
- External helix: galvanized steel.
- Temperature range: -30° C to +100° C.
- Electrical properties: electrical conductivity ensured by the external helix in contact with fittings

Standard/Approval:

- BS 5842. On request: EN 13765 and ADR

Couplings/Fittings:

- All types of swaged couplings
- Semi-symmetrical: aluminium, gun-metal, stainless steel, polypropylene
- Knuckles thread swivel, male and female: aluminium or gun-metal
- Cam action quick couplings (Camlock type)
- Fixed or swivel ISO PN 10, ISO PN 20

Complementary information:

- Fitted lengths are delivered on request with pressure test certificate

输油复合软管 TRELLEX OIL 14

产品编码 No.	内径 in	mm	外径 mm	工作压力 bar	爆破压力 bar	耐负压 bar	弯曲半径 mm	重量 kg/m	包装长度 m
A1-089-1000	1"	25	37.0	14	56	0.9	100	0.84	30
A1-089-1250	1-1/4"	32	43.0	14	56	0.9	120	1.03	30
A1-089-1500	1-1/2"	38	52.0	14	56	0.9	140	1.26	30
A1-089-2000	2"	51	62.0	14	56	0.9	180	1.55	30
A1-089-2500	2-1/2"	63	78.5	14	56	0.9	200	2.51	30
A1-089-3000	3"	80	95.0	14	56	0.9	280	2.88	30
A1-089-4000	4"	102	121.0	14	56	0.9	400	4.70	30
A1-089-6000	6"	152	180.0	14	56	0.9	500	10.80	20
A1-089-8000	8"	204	234.0	14	56	0.9	740	17.60	20
A1-089-10000	10"	254	297.0	14	56	0.9	920	22.50	12

blueFuture

您身边的工业专家