

## 低压水气软管 A4-001



### 应用:

- 本产品可广泛用于那些需要采用一般性用途胶管的工业、建筑和农业领域的排水作业

### 技术参数:

- 内层: Versigard合成橡胶, RMA分级, C等级 (有限耐油性)
- 增强层: 螺旋缠绕的合成纱
- 外层: 黑色或红色的Versigard合成橡胶
- 工作温度: -40° C到99° C

### Applications:

- For a wide range of industrial, construction, and agricultural water discharge applications in which a general service water hose is needed

### Technical description:

- Tube: EPDM synthetic rubber, RMA Class
- Reinforcement: Spiral synthetic yarn
- Cover: Red or black EPDM synthetic rubber
- Temperature: -40°C to 99°C

## 低压水气软管 SURELINE

| 产品编码<br>No. | 内径     |      | 外径<br>mm | 工作压力<br>bar | 重量<br>kg/m | 包装长度<br>m |
|-------------|--------|------|----------|-------------|------------|-----------|
|             | in     | mm   |          |             |            |           |
| A4-001-0250 | 1/4"   | 6.4  | 12.2     | 10.3        | 0.12       | 152.40    |
| A4-001-0380 | 3/8"   | 9.5  | 16.8     | 10.3        | 0.19       | 152.40    |
| A4-001-0500 | 1/2"   | 12.7 | 19.8     | 10.3        | 0.25       | 152.40    |
| A4-001-0630 | 5/8"   | 15.9 | 23.6     | 10.3        | 0.39       | 152.40    |
| A4-001-0750 | 3/4"   | 19.1 | 27.4     | 10.3        | 0.49       | 152.40    |
| A4-001-1000 | 1"     | 25.4 | 35.3     | 10.3        | 0.77       | 137.16    |
| A4-001-1250 | 1-1/4" | 31.8 | 41.4     | 10.3        | 0.85       | 121.92    |
| A4-001-1500 | 1-1/2" | 38.1 | 47.8     | 10.3        | 1.01       | 91.44     |

blueFuture

您身边的工业专家