

绝缘软管 A4-006



应用:

■ 高质量经济的通用胶管，可用于工业气体输送，压缩空气，低压喷绘，以及其它需要中等耐油的场所，不导电，1000伏直流电下每英寸电阻大于1兆欧姆

技术参数:

- 内层: 耐油丁腈胶, RMA分类A级 (高耐油性)
- 增强层: 合成纤维缠绕, 2"合成纱线编织
- 外层: 红色, 蓝色或黑色Chemivic合成胶RMA分类A级 (中等耐油性)
- 工作温度: -29° C到99° C (-20° F到210° F)

Applications:

■ A good-quality, economical general purpose hose for industrial air service, compressor lines, pneumatic tools, low-pressure spray and many other applications where the need for oil resistance is moderate. Non-conductive, minimum electrical resistance greater than one (1) megohm per inch of length of hose at 1000 V DC. Available in 200 PSI working pressures

Technical description:

- Tube: Nitrile synthetic rubber, RMA Class A (High Oil Resistance)
- Reinforcement: Spiral synthetic yarn (3/16"– 1-1/2"), braided synthetic yarn (2")
- Cover: Red, Blue, or Black Buna-N-Vinyl synthetic rubber, RMA Class B
- Temperature: -29 C to 99 C

绝缘软管 VARIFLEX 300

产品编码 No.	内径		外径 mm	工作压力 bar	重量 kg/m	包装长度 m
	in	mm				
A4-006-0250	1/4"	6.4	13.7	20.7	0.21	152.40
A4-006-0310	5/16"	7.9	16.3	20.7	0.27	152.40
A4-006-0380	3/8"	9.5	17.5	20.7	0.28	152.40
A4-006-0500	1/2"	12.7	21.8	20.7	0.39	152.40
A4-006-0630	5/8"	15.9	25.9	20.7	0.49	152.40
A4-006-0750	3/4"	19.1	30.2	20.7	0.63	152.40
A4-006-1000	1"	25.4	38.1	20.7	0.92	137.16
A4-006-1250	1-1/4"	31.8	45.6	17.2	1.25	121.92
A4-006-1500	1-1/2"	38.1	53.2	17.2	1.50	91.44
A4-006-2000	2"	50.8	63.5	20.7	1.52	60.96

blueFuture

您身边的工业专家