

## 硅胶包覆光滑特氟龙软管 AX-007



### 优点:

- 口径: 1/4"-1"(DN6-DN25)
- 温度范围: -70℃至 +200℃
- 标准与防静电内衬可供选择
- 里层为完全平滑的 PTFE 软管, 外覆 SS304 不锈钢编织和铂金硫化白色硅胶层
- 高性能的产品, 具有极好的柔韧性, 表面光滑易擦洗, 零摩擦, 耐高压和耐温广
- 里层及表层均符合 FDA 和 USP 认证

### Advantages:

- Range 1/4"-1"(DN6-DN25)
- Virgin and anti-static liners available.
- smooth bore PTFE hose, with 304 stainless steel over braid and white extruded platinum cured silicone cover
- High performance product offering superb flexibility, smooth wipe clean cover, zero friction, high pressures and a wide temperature range. The solution for a range of application.

### Standard/Approval:

- FDA and USP compliant liner and cover.

## 硅胶包覆光滑特氟龙软管 AX-007

产品编码 No.	Size in.	内径 mm	增强层外径 mm	外径 mm	内衬壁厚 mm	工作压力 bar	爆破压力 bar	弯曲半径 mm	重量 kg/m
AX-007-0250	1/4"	6.71	9.35	15.35	0.75	224	672	76	0.252
AX-007-0310	5/16"	8.41	11.05	17.05	0.65	207	621	102	0.323
AX-007-0380	3/8"	10.29	13.44	19.44	0.65	183	552	133	0.361
AX-007-0500	1/2"	13.30	16.55	22.55	0.90	161	483	152	0.503
AX-007-0630	5/8"	16.76	19.76	24.76	0.90	114	345	178	0.531
AX-007-0750	3/4"	19.81	22.96	27.96	1.00	103	310	203	0.614
AX-007-0870	7/8"	22.10	25.28	30.28	1.00	92	276	229	0.683
AX-007-1000	1"	26.11	29.26	34.26	1.20	80	241	305	0.805

防静电软管可供选择

blueFuture

您身边的工业专家