

硅胶包覆波纹特氟龙软管 AX-008



优点:

- 口径: 1/4"-2"(DN6-DN50)
- 温度范围: -70℃至 +200℃
- 标准与防静电内衬可供选择
- 里层为波纹状的 PTFE 软管, 外覆 SS304 不锈钢编织和铂金硫化白色硅胶层
- 质轻, 柔软, 易清洗, 易排水, 表面光滑易擦洗
- 里层及表层均符合 FDA 和 USP 认证

Advantages:

- Range 1/4"-2"(DN6-DN50)
- Virgin and anti-static liners available.
- Lightweight, high flexible, convoluted PTFE hose, with 304 stainless steel over braid and white extruded platinum cured silicone cover.
- Low profile self-draining liner, easy clean, smooth wipe clean cover, the solution for a wide range of applications.

Standard/Approval:

- FDA and USP compliant liner and covering

硅胶包覆波纹特氟龙软管 AX-008

产品编码 No.	Size in.	内径 mm	增强层外径 mm	外径 mm	内衬壁厚 mm	工作压力 bar	爆破压力 bar	弯曲半径 mm	重量 kg/m
AX-008-0250	1/4"	6.20	9.60	15.60	0.76	172	517	18	0.340
AX-008-0310	5/16"	8.01	12.45	18.45	0.76	155	465	25	0.395
AX-008-0380	3/8"	9.50	13.46	19.46	0.76	138	414	22	0.426
AX-008-0500	1/2"	12.77	18.67	24.67	0.89	103	310	25	0.584
AX-008-0630	5/8"	15.88	22.10	27.10	0.89	83	248	51	0.627
AX-008-0750	3/4"	19.05	24.64	29.64	0.89	69	207	64	0.724
AX-008-0870	7/8"	22.35	28.70	33.70	0.89	57	172	76	0.855
AX-008-1000	1"	25.53	32.89	37.89	1.02	46	138	89	1.036
AX-008-1250	1-1/4"	32.21	40.72	45.72	1.02	34	103	125	1.218
AX-008-1500	1-1/2"	39.37	49.28	54.28	1.02	30	90	150	1.361
AX-008-2000	2"	50.42	59.69	64.69	1.09	23	69	200	1.624

防静电软管可供选择

blueFuture

您身边的工业专家