

# VULCANO PU H 09 ESTERE VB



- 应用于重磨损材料，聚酯型聚氨酯材质的耐磨型软管

## 颜色:

- 半透明

## 温度:

- -40°C + 90°C (短时间可耐 +125° C)

## 应用:

- 可广泛应用于重磨损材料的传输中，如抽吸粉末、颗粒、铁屑、纸屑、织物纤维、锯末、刨花等。

## 技术特性:

- 聚酯型聚氨酯材质，包塑镀铜钢丝螺旋加强。
- 非螺旋处壁厚恒定为0.9毫米
- 内壁平滑，保证物料流动顺畅
- 机械特性卓越，厚实耐磨，即便在低温条件下仍然灵活、柔韧，耐矿物油和多数化学物质。
- 不含卤素
- 不含邻苯二甲酸盐
- 软管两端螺旋钢丝接地可排静电。

- Heavy abrasion, Ester-based Polyurethane, abrasion resistant

## Colour:

- translucent.

## Temperature range:

- -40 C + 90 C (intermittent up to +125 C).

## Applications:

- Ideal for suction highly abrasive media in a wide range of industrial plants: powders, granules, steel dust, paper, textile fibres, pellets, sawdust, woodchips.

## Technical features:

- Ester-based Polyurethane reinforced with PU coated high adhesion coppered steel spiral.
- Constant wall thickness 0.9mm under the spiral.
- Nearly smooth inside to ensure optimization of flow.
- Heavy duty hose with high mechanical properties: strong but very flexible even at low temperatures, excellent resistance to abrasion, mineral oils and most chemicals.
- Halogens free.
- Phthalates free.
- The hose becomes electrically-conductive by grounding the spiral (both ends).



# VULCANO PU H 09 ESTERE

# VB

代码 Part number	内径Φ Inside Φ (mm)	最小壁厚 Min wall th. (mm)	重量 Weight (g/m)	弯曲半径 Bending radius (mm)	耐负压 Vacuum (mH2O)	每卷长度 Roll length (m)	体积 Volume (m3)	桥式卡箍 W2 Double bridge W2
VB0102000000	20*	0.9	170	25	5.0	20	0.040	-
VB0102500000	25*	0.9	215	30	5.0	20	0.040	-
VB0103000000	30*	0.9	260	35	5.0	20	0.050	-
VB0103200000	32*	0.9	280	35	5.0	20	0.050	-
VB0103500000	35*	0.9	300	40	5.0	20	0.060	-
VB0103800000	38	0.9	290	40	5.0	20	0.060	-
VB0104000000	40	0.9	300	50	5.0	20	0.070	-
VB0104500000	45*	0.9	390	50	5.0	20	0.070	-
VB0105100000	51	0.9	435	60	4.0	20	0.100	-
VB0105500000	55*	0.9	470	65	3.5	20	0.120	-
VB0106000000	60	0.9	510	70	3.0	20	0.130	-
VB0106300000	63	0.9	530	70	3.0	20	0.130	-
VB0106500000	65*	0.9	545	70	3.0	20	0.180	-
VB0107000000	70	0.9	675	80	3.0	20	0.200	-
VB0107600000	76	0.9	730	90	3.0	20	0.240	-
VB0108000000	80	0.9	765	90	3.0	20	0.260	F2 W2 076.0 090.0
VB0109000000	90	0.9	855	100	2.5	20	0.290	F2 W2 076.0 090.0
VB0110200000	102	0.9	965	120	2.0	15	0.320	F2 W2 100.0 127.0
VB0111000000	110*	0.9	1035	130	2.0	15	0.340	F2 W2 100.0 127.0
VB0111500000	115*	0.9	1080	135	1.5	15	0.360	F2 W2 100.0 127.0
VB0112000000	120	0.9	1125	140	1.5	15	0.370	F2 W2 100.0 127.0
VB0112700000	127	0.9	1370	150	1.5	15	0.390	F2 W2 100.0 127.0
VB0113000000	130*	0.9	1405	150	1.5	15	0.400	F2 W2 130.0 190.0
VB0114000000	140	0.9	1505	160	1.0	15	0.640	F2 W2 130.0 190.0
VB0115000000	150*	0.9	1610	170	1.0	15	0.690	F2 W2 130.0 190.0
VB0115200000	152	0.9	1630	170	1.0	15	0.700	F2 W2 130.0 190.0
VB0116000000	160	0.9	1715	180	1.0	15	0.730	F2 W2 130.0 190.0
VB0118000000	180	0.9	1720	210	0.5	15	0.970	F2 W2 130.0 190.0
VB0120000000	200	0.9	1905	230	0.5	15	1.080	F2 W2 200.0 230.0
VB0122000000	220*	0.9	2090	260	0.3	10	1.180	F2 W2 200.0 230.0
VB0122800000	228*	0.9	2160	260	0.3	10	1.220	F2 W2 200.0 230.0
VB0125000000	250*	0.9	2365	290	0.3	10	1.330	F2 W2 250.0 330.0
VB0125400000	254	0.9	2400	290	0.3	10	1.350	F2 W2 250.0 330.0
VB0127900000	279*	0.9	2870	320	0.2	10	1.480	F2 W2 250.0 330.0
VB0130000000	300*	0.9	3080	350	0.2	10	1.590	F2 W2 250.0 330.0
VB0130500000	305	0.9	3130	350	0.2	10	1.610	F2 W2 250.0 330.0
VB0131500000	315*	0.9	3230	350	0.2	10	1.660	F2 W2 250.0 330.0
VB0135000000	350*	0.9	4075	410	0.1	A richiesta (max 10m) pz dritti/On request (max 10m) straight pieces		F2 W2 350.0 410.0
VB0135600000	356*	0.9	4145	410	0.1			F2 W2 350.0 410.0
VB0140000000	400*	0.9	4645	ND	0.1			F2 W2 350.0 410.0
VB0145000000	450*	0.9	6535	ND	0.1			

\* Available on request, contact our sales office for more info and quantities

\* 如有需要, 请与我们的销售办公室联系以获取更多信息和数量

The technical data here reported were measured at 23° c with 50% humidity

技术参数均在23°C 50%湿度下测量

