

高温模具管

A2-501



应用:

- 适用于注塑机模具冷却，及通用行业的热热水排放场合等

技术参数:

- 内胶层: 黑色EPDM橡胶, 耐热耐老化
- 增强层: 高强度合成纤维
- 外胶层: EPDM橡胶, 软管外胶有红, 黑, 蓝色选择
- 温度: -40°C至+160°C

Applications:

- Specifically designed for coolants in plastic injection moulds, and discharge of thermal hot water in general industries

Technical description:

- Inner tube: black EPDM rubber, heat and ageing resistance
- Reinforcement: High strength synthetic fiber
- Cover: EPDM rubber, red, black and blue colours are available
- Temp. Range: -40°C to +160°C

高温模具管 TFW

产品编码 No.	内径		外径 mm	工作压力 bar	包装长度 m
	in	mm			
A2-501-0380-RED	3/8"	9.5	15	15	50
A2-501-0380-BLK	3/8"	9.5	15	15	50
A2-501-0380-BLU	3/8"	9.5	15	15	50
A2-501-0500-RED	1/2"	13.0	19	15	50
A2-501-0500-BLK	1/2"	13.0	19	15	50
A2-501-0500-BLU	1/2"	13.0	19	15	50
A2-501-0750-BLK	3/4"	19.0	27	15	30
A2-501-0750-RED	3/4"	19.0	27	15	30

blueFuture

您身边的工业专家