


# 食品级PVC钢丝管

## B2



### 应用:

液体食品、果汁、一般水性食品的排吸。适用于酒精度不大于50% 液体的输送。

### 颜色:

- 透明

### 温度:

- -10°C至 + 60°C

### 特性:

- 采用 BIO-VINYL 环保型PVC原料，高强度聚酯纤维网布衬垫加强。
- 完全不添加邻苯二甲酸或其他合成增塑剂。

### 认证:

- FDA 21CFR 177.2600, EU10/2011

### Applications:

Ideal solution for suction and delivery of food liquids, beverages, fruit juices, wine and liquors with up to 50% alcohol concentration.

### Colour:

- Transparent with polyester reinforcement

### Temperature range:

- -10°C + 60°C

### Features:

- Flexible hose produced with Biovinyl™ and high tenacity polyester reinforcement.
- Completely free of phthalates. Resistant to several chemicals and to weather conditions.

### Standards:

- FDA 21CFR 177.2600, EU10/2011

## 食品级PVC钢丝管

## B2

产品编码 No.	内径 in	内径 mm	外径 mm	工作压力 bar	爆破压力 bar	耐负压 mH2O	弯曲半径 mm	体积 m <sup>3</sup>	重量 kg/m	包装长度 m
B2-0240	*	6.0	12.2	5.0	25.0	9.5	30	0.019	0.130	60
B2-0310	5/16"	8.0	14.2	5.0	25.0	9.5	40	0.022	0.160	60
B2-0380	3/8"	10.0	16.0	7.0	35.0	8.5	50	0.028	0.185	60
B2-0470	*	12.0	18.0	7.0	35.0	8.5	50	0.033	0.210	60
B2-0500	1/2"	13.0	19.0	7.0	35.0	8.5	60	0.038	0.220	60
B2-0550	*	14.0	20.0	7.0	35.0	8.5	60	0.039	0.230	60
B2-0630	5/8"	16.0	22.4	7.0	35.0	8.5	70	0.048	0.275	60
B2-0710	*	18.0	24.4	6.0	30.0	8.5	80	0.067	0.300	60
B2-0790	*	20.0	27.0	6.0	30.0	8.5	90	0.082	0.355	60
B2-0870	7/8"	22.0	29.0	6.0	30.0	8.5	100	0.093	0.390	60
B2-1000	1"	25.0	33.0	6.0	30.0	8.5	110	0.111	0.510	60
B2-1180	*	30.0	38.0	5.0	25.0	8.5	140	0.151	0.600	60
B2-1250	1-1/4"	32.0	40.4	5.0	25.0	8.5	140	0.171	0.665	60
B2-1380	1-3/8"	35.0	43.4	5.0	25.0	8.5	160	0.188	0.710	60
B2-1500	1-1/2"	38.0	47.0	5.0	25.0	8.5	170	0.114	0.805	30
B2-1580	1-9/16"	40.0	49.2	5.0	25.0	8.5	180	0.125	0.880	30
B2-1770	*	45.0	54.8	4.0	20.0	8.0	200	0.177	1.135	30
B2-1970	*	50.0	60.0	4.0	20.0	8.0	230	0.213	1.275	30
B2-2360	2-3/8"	60.0	71.8	3.5	17.5	8.0	270	0.285	1.745	30
B2-2500	2-1/2"	63.0	74.8	3.5	17.5	8.0	280	0.281	1.830	30
B2-2760	*	70.0	82.0	3.5	17.5	7.0	320	0.342	2.070	30
B2-3000	3"	76.0	88.2	3.5	17.5	7.0	340	0.489	2.275	30
B2-3150	*	80.0	92.2	3.5	17.5	7.0	360	0.357	2.400	20
B2-3540	*	90.0	103.0	3.0	15.0	7.0	410	0.415	3.025	20
B2-4000	4"	102.0	115.0	2.0	10.0	7.0	460	0.517	3.490	20
B2-4130	*	105.0	118.0	2.0	10.0	7.0	470	0.531	3.600	20
B2-4330	*	110.0	127.4	1.6	8.0	9.0	550	0.612	4.770	20
B2-4720	*	120.0	137.4	1.2	6.0	9.0	600	0.686	5.170	20
B2-5000	5"	127.0	144.4	1.2	6.0	9.0	640	0.739	5.465	20
B2-6000	6"	151.0	169.6	1.2	6.0	9.0	760	1.303	6.855	20

