

铂金硫化钢丝硅胶管PURE SW

A5-033



应用:

食品、饮料、化妆品、制药等高洁净行业, 可耐一定真空, 可进行CIP及SIP清洗。

技术参数:

- 铂金硫化硅胶管, 4层编织, 内置 SS316 不锈钢丝增强
- 标准为半透明, 可定制其他颜色
- 工作温度: -60°C 至 +200°C

适用标准及认证:

- GB4806.7-2016
- GB31604.30-2016
- GB9685-2016
- FDA 21CFR 177.2600
- USP CLASS VI
- ISO 10993
- EP. 3.1.9
- Italy Gazzetta Ufficiale-1973
- German BGVV XVA&LIIA
- France Journal officiel-Brochure 1227

Applications:

For food, beverages, cosmetics, medicine, pharmaceutical industries. It is recommended for vacuum. Suitable for CIP and SIP cleaning.

Technical Description:

- Manufactured from High purity platinum cured Silicone with AISI 316 stainless steel helix and 4 layers of polyester reinforcement
- Semitransparent (Coloured covers available)
- Temperature range : -60°C to +200°C

Standard/Approval:

- GB4806.7-2016
- GB31604.30-2016
- GB9685-2016
- FDA 21CFR 177.2600
- USP CLASS VI
- ISO 10993
- EP. 3.1.9
- Italy Gazzetta Ufficiale-1973
- German BGVV XVA&LIIA
- France Journal officiel-Brochure 1227

铂金硫化钢丝硅胶管 PURE SW

产品编码 No.	内径 in	mm	外径 mm	工作压力 bar	爆破压力 bar	真空度 bar	弯曲半径 mm	重量 kg/m	包装长度 m
PURE SW-0500	1/2"	12.7	27	10	40	0.90	45	0.4	4
PURE SW-0630	5/8"	15.8	31	10	40	0.90	50	0.6	4
PURE SW-0750	3/4"	19.05	33.4	10	40	0.90	65	0.7	4
PURE SW-1000	1"	25.4	39.5	10	40	0.90	80	0.88	4
PURE SW-1250	1-1/4"	31.8	45.5	10	40	0.90	120	1	4
PURE SW-1500	1-1/2"	38.1	52.4	10	40	0.90	150	1.41	4
PURE SW-2000	2"	50.8	65.5	10	40	0.90	180	1.66	4
PURE SW-2500	2-1/2"	63.5	75.9	10	40	0.90	220	1.9	4
PURE SW-3000	3"	76.2	88.6	4	16	0.90	250	2.43	2
PURE SW-4000	4"	101.6	114	3	12	0.90	360	2.95	2

