

# 耐油网纹管 ST型

## PX-018



### 应用:

- 作为一般配管用, 适用于水、油、药品、空气等各种流体
- 耐油性优异, 柔软性持久, 耐久性良好, 使用寿命长
- 柔软性良好, 配管简便
- 透明度高, 可确认流体, 放心可靠
- 符合RoHS2修正规制, 安全放心

### 技术参数:

- 主材质: 软质聚氯乙烯
- 加强材料: 聚酯丝
- 颜色: 绿色透明带图案条+带蓝色竖线
- 包装: ST-6~25: 筒卷 ST-32~75: 薄膜卷
- 工作温度: -5°C至+60°C

### 优点:

- 柔软
- 透明
- 耐油
- 泵送用

### Applications:

- As a general piping, it is suitable for various fluids such as water, oil, medicine, air, etc.
- Excellent oil resistance, long-lasting flexibility, good durability and long service life
- Good flexibility and easy piping
- High transparency, fluid can be confirmed, rest assured and reliable
- Comply with RoHS2 revised regulations, safe and secure

### Technical description:

- Main material: soft polyvinyl chloride
- Reinforcing material: polyester silk
- Color: green transparent patterned strip + blue vertical line
- Packing: ST-6-25: Reel ST-32-75: Film reel
- Working temperature: -5 C to +60 C

### Advantages:

- soft
- Transparent
- Oil resistant
- For pumping

## 耐油网纹管 ST型

## PX-018

产品编码 No.	内径		外径 mm	使用压力 Mpa	标准长度重量 kg/卷	标准长度 m	最小弯曲半径 mm
	in	mm					
PX-018-6	1/4"	6	10.5	0~1.0	8	100	25
PX-018-8	5/16"	8	13	0~1.0	11	100	35
PX-018-9	3/8"	9	15	0~1.0	15	100	45
PX-018-12	1/2"	12	18	0~0.8	19	100	60
PX-018-15	5/8"	15	22	0~0.8	27	100	90
PX-018-19	3/4"	19	26	0~0.6	16	50	130
PX-018-22	27/32"	21.5	28.5	0~0.6	19	50	125
PX-018-25	1"	25	33	0~0.6	25	50	150
PX-018-32	1-1/4"	32	41	0~0.4	28	40	192
PX-018-38	1-1/2"	38	48	0~0.4	36	40	228
PX-018-48	1-7/8"	48	58	0~0.4	40	40	290
PX-018-50	2"	50	62	0~0.3	54	40	300
PX-018-63	2-1/2"	63	80	0~0.3	53	20	600
PX-018-75	3"	75	92	0~0.3	62	20	800

