

UPE化学品排吸管

DSC UPE



应用:

- 适用于输送和抽吸绝大多数侵蚀性化学品，溶剂，醇类，可输送浓度达 98% 的酸和化学品。

技术参数:

- 内层：白色，超高分子量聚乙烯，浅色合成橡胶，黑色导电条纹
- 增强层：高强度合成纤维、螺旋钢丝
- 外层：蓝色，三元乙丙橡胶，耐磨，耐臭氧，耐气候老化（其他颜色可选）
- 工作温度：-40°C ~ +99°C

Applications:

- Hard wall hose suitable for handling a wide range of aggressive chemicals, solvents, alcohols, good for acids/chemicals in high concentration up to 98%.

Technical description:

- Tube: White, UHMWPE, light colored synthetic rubber with black strip, anti-static
- Reinforcement: High tension textile fabric, helix steel wire
Cover: Blue, EPDM, wear resistance, ozone resistance, weather/aging resistance (coloured covers available)
Temperature range : - 40°C to + 99°C

UPE化学品排吸管 DSC UPE

产品编码 No.	规格 (inch)	内径 (mm)	外径 (mm)	工作压力 (bar)	工作压力 (psi)	爆破压力 (bar)	爆破压力 (psi)	耐负压 (bar)	最小弯曲半径 (mm)	重量 (kg/m)	包装长度 (m)
DSC UPE-0075	3/4"	19	30	16	240	64	960	0.9	130	0.7	60
DSC UPE-0100	1"	25	36	16	240	64	960	0.9	150	0.9	60
DSC UPE-0125	1-1/4"	32	43	16	240	64	960	0.9	200	1.1	60
DSC UPE-0150	1-1/2"	38	49	16	240	64	960	0.9	225	1.3	60
DSC UPE-0200	2"	51	62	16	240	64	960	0.9	275	1.7	60
DSC UPE-0250	2-1/2"	64	76	16	240	64	960	0.9	350	2.1	60
DSC UPE-0300	3"	76	89	16	240	64	960	0.9	400	2.8	60
DSC UPE-0400	4"	102	116	16	240	64	960	0.9	800	3.8	60
DSC UPE-0500	5"	127	144	16	240	64	960	0.9	1300	6.5	60
DSC UPE-0600	6"	152	171	16	240	64	960	0.9	1600	8.1	60

