

超高压光滑特氟龙软管PSE

A5-026



应用:

这款超高压特氟龙管专门为对强度、可靠性和长期性要求比较高的应用设计，是输送热油、粘合剂、密封剂、磷酸盐和化学品的理想选择。

优点:

- 光滑食品级内壁，能有效抑制细菌滋长
- 具有良好的机械抗力，抗紫外线，耐老化

技术参数:

- 里层为光滑的透明PTFE软管，外覆双层304不锈钢编织
- 工作温度：-70°C至+260°C
- 标准与防静电内衬可供选择

适用标准及认证:

- 符合FDA 21CFR 177.1550认证

Applications:

These lightweight, high pressure hoses are specially constructed for applications requiring strength, reliability and long term performance. It is good choice for conveying hot oils, adhesives, sealants, phosphates and chemicals.

Advantages:

- Smooth food - grade inner wall can effectively inhibit bacterial growth
- Good mechanical resistance,Uv resistance and aging resistanc

Technical Description:

- The inner layer is smooth transparent PTFE hose, and the outer layer is covered with 304 stainless steel braid
- Temperature range: -70°C to + 260°C
- Virgin and anti-static liners are available

Standard/Approval:

- FDA 21CFR 177.1550

超高压光滑特氟龙软管

PSE

产品编码 No.	内径 in	内径 mm	外径 mm	内衬壁厚 mm	工作压力 bar	爆破压力 bar	弯曲半径 mm
PSE-0250	1/4"	5.64	9.53	1.03	345	1103	65
PSE-0380	3/8"	7.82	12.01	1.03	345	1103	90
PSE-0500	1/2"	10.19	15.24	1.2	345	1103	100
PSE-0630	5/8"	12.57	18.03	1.3	345	1103	120
PSE-0750	3/4"	15.67	24.64	1.3	345	1103	160
PSE-1000	1"	22.02	31.75	1.4	345	1103	200
PSE-1250	1-1/4"	28.58	40.64	1.4	345	1103	250
PSE-1500	1-1/2"	34.93	48.77	1.8	276	827	356

